

# Xerox<sup>®</sup> Phaser<sup>®</sup> 6510 Colour Printer



System Specifications	Phαser® 6510N	Phaser® 6510DN	Phaser® 6510DNI
One-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 30 ppm colour and black-and-white Up to 28 ppm colour and black-and-white Up to 24 ppm colour and black-and-white		
Two-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	NA	Up to 19 ppm colour and black-c Up to 18 ppm colour and black-c Up to 17 ppm colour and black-c	and-white
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month		
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 3,000 pages		
Processor	733 MHz		
Memory	1 GB		
Connectivity	10/100/1000Base-T Ethernet High-Speed USB 3.0		10/100/1000Base-T Ethernet High-Speed USB 3.0 Wi-Fi 802.11n Wi-Fi Direct <sup>®</sup>
Device Specifications			
Electrical Requirements			
North America	Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A		
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50 Hz +/- 3 Hz, 6A		
Power Consumption			
Operation <sup>4</sup>	120V: Maximum 380 watts 220V: Maximum 350 watts		
Standby Mode <sup>4</sup>	120V: Maximum 41 watts 220V: Maximum 44 watts		
Power Off Mode <sup>4</sup>	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts		
Sleep Mode <sup>4</sup>	120V: Maximum 0.9 watts 220V: Maximum 1.0 watts		
Warm-up (from Sleep Mode)	As fast as 26 seconds		
Operating Environment			
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C		
Required Relative Humidity	15 % to 85 %		
Sound Power Levels Operating Standby	6.76 B or less 4.00 B or less		

Font Capability

Xerox® Mobile Express Driver®

Xerox® Global Print Driver®

136 PostScript fonts 88 PCL fonts

reduce mobile support calls to IT.

	<b>Sound Pressure Levels</b> Operating Standby	51.9 dB(A) or less 24.9 dB(A) or less			
aser® 6510DNI 16.5 in. / 420 mm 19.6 in. / 499 mm 13.7 in. / 347 mm 52.5 lb. / 2. Desheet Paper Tray 16.5 in. / 420 mm 18.3 in. / 465 mm 5.9 in. / 150 mm 14.8 lb. / 6. mensions and Weights Width Depth Height Weight ackaged) 14.3 in. / 634 mm 22.8 in. / 580 mm 19.9 in. / 505 mm 64.4 lb. / 2. Desheet Paper Tray 21.1 in. / 535 mm 23 in. / 584 mm 9.8 in. / 248 mm 18.7 lb. / 8. Triffications view the latest list of certifications, go to www.xerox.com/OfficeCertifications.  Int st. Print-Out Time As fast as 12 seconds colour and black-and-white Up to 1200 x 2400 dpi ge Description Languages Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF  Intimum Print Area 4 mm edge of paper mt Features Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page Nup Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, IPEG, TIFF, XPS  windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Citrix® Redhat® Enterprise Linux® IBMP AIX® 5 HP-UX® 11.92 Oracle® Solaris 9, 10 Fedora Core 12-15	Dimensions and Weights (unpackaged)	Width	Depth	Height	Weight
16.5 in. / 420 mm 18.3 in. / 465 mm 5.9 in. / 150 mm 14.8 ib. / 6. mensions and Weights (Adaged) Width Depth Height Weight (Adaged) asser® 6510N, DN and DNI 14.3 in. / 634 mm 22.8 in. / 580 mm 19.9 in. / 505 mm 64.4 ib. / 20. sheet Paper Tray 21.1 in. / 535 mm 23 in. / 584 mm 9.8 in. / 248 mm 18.7 ib. / 8. triffications view the latest list of certifications, go to www.xerox.com/OfficeCertifications.  ***Tiffication**  **Tiffication**  **Tiffi	Phaser® 6510N and DN	16.5 in. / 420 mm	19 in. / 483 mm	13.7 in. / 347 mm	52.5 lb. / 23.8 kg
mensions and Weights (ackaged)  Width  Depth  Height  Weight (ackaged)  14.3 in. / 634 mm  22.8 in. / 580 mm  19.9 in. / 505 mm  64.4 lb. / 2²  Desheet Paper Tray  21.1 in. / 535 mm  23 in. / 584 mm  9.8 in. / 248 mm  18.7 lb. / 8²  Width  Weight  18.7 lb. / 8²  Width  Posheet Paper Tray  21.1 in. / 535 mm  23 in. / 584 mm  9.8 in. / 248 mm  18.7 lb. / 8²  Wiew the latest list of certifications, go to www.xerox.com/OfficeCertifications.  ***  ***  ***  ***  ***  ***  ***	Phaser® 6510DNI	16.5 in. / 420 mm	19.6 in. / 499 mm	13.7 in. / 347 mm	52.5 lb. / 23.8 kg
secree 5510N, DN and DNI 14.3 in. / 634 mm 22.8 in. / 580 mm 19.9 in. / 505 mm 64.4 lb. / 22.0 o-sheet Paper Tray 21.1 in. / 535 mm 23 in. / 584 mm 9.8 in. / 248 mm 18.7 lb. / 8. rtifications  ***Trifications**  ***Trific	550-sheet Paper Tray	16.5 in. / 420 mm	18.3 in. / 465 mm	5.9 in. / 150 mm	14.8 lb. / 6.7 kg
18.7 lb. / 8. mitifications  18.8 lb. / 8. mitifications  18.7 lb. / 8. m	Dimensions and Weights (packaged)	Width	Depth	Height	Weight
ritifications  view the latest list of certifications, go to www.xerox.com/OfficeCertifications.  ***st-Print-Out Time**  As fast as 12 seconds colour and black-and-white  **pt-int-Out Time**  As fast as 12 seconds colour and black-and-white  **pt-int-Out Time**  Adobe® PostScript® 3™ PCL® 5e, 6 PDF  **TIFF**  **pximum Print Area**  4 mm edge of paper  Banner Sheets  Booklet Print  Cover / Separators  Draft Mode  Fit to Page  N-up  Overlays  PANTONE® Colour Calibrated Solid-colour Simulations  Personal Print  Proof Print  RAM Collation  Run Black  Saved Print  Secure Print  Watermarks  **watermarks**  **stypported file formats: PDF, JPEG, TIFF, XPS**  **print Time**  **stypported file formats: PDF, JPEG, TIFF, XPS**  **windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012  **Mac OS® version 10.10 and higher**  Citrix®  Redhate® Enterprise  Linux®  IBM® AIX® 5  HP-UX® 11iv2  Oracle® Solaris 9, 10  Fedora Core 12-15	Phaser® 6510N, DN and DNI	14.3 in. / 634 mm	22.8 in. / 580 mm	19.9 in. / 505 mm	64.4 lb. / 29.2 kg
wiew the latest list of certifications, go to <a href="https://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .  Int  st-Print-Out Time  As fast as 12 seconds colour and black-and-white  Up to 1200 x 2400 dpi  Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF  Eximum Print Area  4 mm edge of paper  Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  aupported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracl® Solains 9, 10 Fedora Core 12-15	550-sheet Paper Tray	21.1 in. / 535 mm	23 in. / 584 mm	9.8 in. / 248 mm	18.7 lb. / 8.5 kg
st-Print-Out Time  As fast as 12 seconds colour and black-and-white  Up to 1200 x 2400 dpi  ge Description Languages  Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF  eximum Print Area  4 mm edge of paper  Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print RAM Collation Run Black Saved Print Secure Print Watermarks  Int from USB  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Certifications				
st-Print-Out Time  As fast as 12 seconds colour and black-and-white  Up to 1200 x 2400 dpi  Ge Description Languages  Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF  Eximum Print Area  4 mm edge of paper  Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Int from USB  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	To view the latest list of certificat	ions, go to www.xerox.co	m/OfficeCertifications.		
nt Resolution  Up to 1200 x 2400 dpi  Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF  Iximum Print Area  4 mm edge of paper  Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print RAM Collation Run Black Saved Print Secure Print Watermarks  Trom USB  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Print				
Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF  Iximum Print Area  4 mm edge of paper  Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  ant from USB  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhar® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	First-Print-Out Time	As fast as 12 seconds	As fast as 12 seconds colour and black-and-white		
PCL® 5e, 6 PDF TIFF  Iximum Print Area  4 mm edge of paper  Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Print Resolution	Up to 1200 x 2400 dpi			
Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  and Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Page Description Languages	PCL <sup>®</sup> 5e, 6 PDF	PCL <sup>©</sup> 5e, 6 PDF		
Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks  supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS  erating Systems  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Maximum Print Area	4 mm edge of paper	4 mm edge of paper		
Supported file formats: PDF, JPEG, TIFF, XPS  Windows®, 7, 8, 10, Server 2000, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Print Features	Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Co Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print	Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Colour Calibrated Solid-colour Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print		
Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15	Print from USB				
3032	Operating Systems	Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10			

Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver®be automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers

for each location, store application print settings for use on any printer in any network, and greatly

A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for endusers, reducing the number of support calls, and simplifying print services management.

Mobile Solutions and Mobile Devi	ce Apps	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone <sup>®</sup> or iPad <sup>®</sup> with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.	
Mopriα <sup>®</sup> Certified	Mopria certification ensures you can print wirelessly from your Mopria supported (Android) smart phone, tablet and other mobile devices instantly and easily.	
Xerox® Print Service Plug-in for Android™ (Free αt Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox <sup>®</sup> Wireless Print Solutions Adapter seamlessly connects your Xerox <sup>®</sup> printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA.	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security — for any brand printer, anywhere. Xerox® Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow.  • Xerox® Workplace Suite: On-site, your server  • Xerox® Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit www.xerox.com/Mobility.	
Security		
Security Features	Simultaneous HTTP and HTTPS support IPsec 802.1x Authentication S/MIME IP Filtering Secure Print SNMP v3 LDAP (SASL)	

Paper Handling			
Bypass Tray			
Capacity <sup>3</sup>	50 sheets		
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm		
Mediα Types	Bond Plain Cardstock Custom Envelopes Glossy Cardstock Hole Punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled		
Tray 1			
Capacity <sup>3</sup>	250 sheets		
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14	in. / 76 x 147 mm to 216 x 356 mm	
Weights	16 lb. bond to 65 lb. cover / 60 to 1	76 gsm	
Media Types	Bond Plain Cardstock Custom Envelopes Glossy Cardstock Hole Punched Labels Letterhead Lightweight Cardstock Preprinted Recycled		
Optional Tray 2			
Capacity <sup>3</sup>	550 sheets		
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 191 mm to 216 x 356 mm		
Weights	16 lb. bond to 65 lb. cover / 60 to 1	76 gsm	
Mediα Types	Bond Plain Cardstock Custom Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Preprinted Recycled		
Total Capacity			
Device Standard Capacity <sup>3</sup>	300 sheets		
Device Total Capacity <sup>3</sup>	850 sheets	850 sheets	
Paper Output			
Output Capacity <sup>3</sup>	150 sheets		
Automatic 2-Sided	NA S	tandard	

Device Management		
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP v2/3, WINS, DHCP Autonet, TLS, SNTP, MDNS	
Xerox® CentreWare® Web		
	<ul> <li>A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>	
Xerox® Embedded Web Server - Ir	ntegrated Device Web Page	
Device Status	<ul> <li>Tray Status / Contents</li> <li>Consumables Status</li> <li>Billing / Usage</li> <li>Quick Links</li> </ul>	
Job Submission	Print-ready files (PS, PCL®, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.	
Browsers	Microsoft <sup>®</sup> Internet Explorer 11 Microsoft Edge <sup>™</sup> 38 Mozilla <sup>™</sup> Firefox <sup>®</sup> 48 Apple <sup>®</sup> Sαfαri <sup>®</sup> 9.1 Google Chrome <sup>™</sup> 52	
Remote Print Services		
Xerox® Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox <sup>®</sup> Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
Troubleshooting and Diagnostic Support	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
What's In The Box		
	<ul> <li>Phaser® 6510 Colour Printer</li> <li>Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow): 1,000 print capacity<sup>5</sup>; Black: 1,500 print capacity<sup>5</sup></li> <li>Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers and Warranty Statement)</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power Cord</li> </ul>	

Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages <sup>5</sup> Magenta: 4,300 standard pages <sup>5</sup> Yellow: 4,300 standard pages <sup>5</sup>	106R03693 106R03694 106R03695
High Capacity Print Cartridges	Black 5,500 standard pages <sup>5</sup> Cyan: 2,400 standard pages <sup>5</sup> Magenta: 2,400 standard pages <sup>5</sup> Yellow: 2,400 standard pages <sup>5</sup>	106R03488 106R03485 106R03486 106R03487
Standard Capacity Print Cartridges	Black: 2,500 standard pages <sup>5</sup> Cyan: 1,000 standard pages <sup>5</sup> Magenta: 1,000 standard pages <sup>5</sup> Yellow: 1,000 standard pages <sup>5</sup>	106R03484 106R03481 106R03482 106R03483
Drum Cartridges	Black: 48,000 pages <sup>6</sup> Cyan: 48,000 pages <sup>6</sup> Magenta: 48,000 pages <sup>6</sup> Yellow: 48,000 pages <sup>6</sup>	108R01420 108R01417 108R01418 108R01419
Waste Cartridge	30,000 pages <sup>6</sup>	108R01416
Accessories		
550-sheet Paper Tray		097S04765
Wireless Network Adapter		497K16750
Cabinet (includes Caster Base)		097S04994

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.

© 2019 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, CentreWare®, Global Print Driver®, Mobile Express Driver® and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency (DN and DNI configurations). ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. The information in this brochure is subject to change without notice. Updated 2/19 BR19948 65XSS-011H







www.asep.sk | www.vytlacimevsetko.sk





首+421 2/6353 7976 



亩+421 2/5244 4229 ■ tlac@asep.sk







<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sastulined on a regular models.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>6</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.